

Tanacoat

Enhanced durability for exterior timbers



Tanacoat is a non film forming premium penetrating wood oil. The low sheen penetrating wood oil nourishes and enriches the natural timber colour and grain and provides protection to the timber against the effects of sunlight and moisture.

Tanacoat is especially formulated to penetrate the timber in a single pack application and with enhanced UV absorbers and water repellants to reduce the effects of weathering and provides resistance to the growth of mould and algae.

Tanacoat provides consumers with the ability to maintain and enhance the durability of all their outdoor timber products and is ideal for decks, pergolas, fences, gates, retaining walls and garden furniture.

Tanacoat has also been scientifically tested and shown to effectively seal treated timber.

To find your nearest **Tanacoat** supplier or for further information, contact the Lonza team.

Phone: 1300 650 636

Q. What exterior timbers can I use TANACOAT on?

TANACOAT is suitable for use on all popular timbers including Spotted Gum, Iron Bark, Black Butt, Cedar, Meranti, Jarrah, Merbau, Kwila, Brush Box, Tasmanian Oak, Teak, Tallow wood, Pine and Oregon.

Also suitable for sealing Treated Pine and Engineered Wood Products.

Q. What surface preparation is required?

Hardwoods

1. Hardwoods should be left uncoated until the timber first starts to take on a slight greying effect. Depending on timber species this can take up to 6 months
2. Surface must be completely clean and dry before application. If the timber has been recently wetted (e.g. due to rain) leave at least 3 days to dry.

Softwoods

1. Softwoods should be left uncoated for 7 days after installation to allow the timbers to adjust to the surrounding climatic conditions.
2. Surface must be completely clean and dry before application. If the timber has been recently wetted (e.g. due to rain) leave at least 3 days to dry.

Restoration

1. For surfaces that are starting to grey or have stopped beading water simply reapply TANACOAT.
2. For surfaces that have experienced severe weathering or are affected by surface mould or algae, clean with a timber cleaning product.

Q. How can TANACOAT be applied?

1. Stir thoroughly before use.
2. Brush or Pad applicator:
Apply evenly with the grain including exposed edges and ends.
3. Spray:
Suitable for application by all standard spray equipment.
It is advisable to backbrush applied material to ensure complete wetting of the timber.
4. Excess TANACOAT must be wiped off surface.

Q. What are the drying and recoat times for TANACOAT?

1. All timings are based on 25°C and 50% humidity. Cooler or humid conditions may require longer.
2. Touch Dry - Up to 5 hrs
3. Recoat - allow minimum of 6 hrs.
Only required if surface is very porous.
4. Walk on - 12 hrs after coating.
5. IMPORTANT

Do not apply when rain or heavy dew is expected during the drying period.
Excess material must be wiped off surface.

Q. Does TANACOAT require thinning?

No, Thinning is not required.

Q. How do I clean up after using TANACOAT?

Clean up using mineral turpentine.

Q. What area will TANACOAT cover?

TANACOAT will cover approximately 8- 12 square metres per litre depending on surface porosity.

Q. How do I Dispose of left over TANACOAT ?

Do not pour left over product down drain. Keep unwanted product in sealed containers for disposal via collection facilities. When dry, recycle container where possible. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

Q. What safety precautions should I take with TANACOAT?

Risk: Irritating to skin. May cause sensitization by skin contact. May cause lung damage if swallowed.

Keep out of reach of children. Avoid contact with skin and eyes. Provide adequate ventilation. If using indoors keep windows and doors open during use and while drying. Avoid using while smoking or around ignition sources..

www.tanalised.com



Australia

Lonza Wood Protection

1300 650 636

Tanacoat and Tanalised are registered trademarks of Arch Wood Protection (Aust) Pty Limited a Lonza owned Company. © Copyright all rights reserved.

Lonza Tanacoat Flyer.

Aug 2013 v2

The information contained herein is believed to be correct and corresponds to the latest state of scientific and technical knowledge. However, no warranty is made, either expressed or implied, regarding its accuracy or the results to be obtained from the use of such information. Some products may not be available in all markets or for every type of application. Any user must make his own determination and satisfy himself that the products supplied by Lonza Group Ltd and the information and recommendations given by Lonza Group Ltd are (i) suitable for intended process or purpose, (ii) in compliance with environmental, health and safety regulations, and (iii) will not infringe any third party's intellectual property rights.

© 2013 Lonza Ltd